

0.75M Flyaway Antenna

Applications

1. Sudden public events and all kinds of disasters on-site information gathering
2. Relief in disaster
3. Public security, military, government, oil, water conservancy, electricity, finance and other important sectors of the country
4. Coverage in remote areas and vast rural areas
5. Field operations, exploration, military police and news media

| | | |
|---|----|---------------------------|
| Antenna Aperture | | 0.75m Flyaway Antenna |
| VSWR | Tx | 1. 25:1 |
| | Rx | 1. 25:1 |
| 3dB beamwidth | Tx | 1. 9° |
| | Rx | 2. 1° |
| Polarization | | Linear |
| Operation Frequency | Tx | 14–14. 5 GHz |
| | Rx | 12. 25–12. 75GHz |
| Cross-polarization | Tx | >30dB |
| | Rx | >30dB |
| Gain | Tx | >38. 5 dBi |
| | Rx | >37. 2 dBi |
| Power Capacity | | 100W |
| Feed Interface | | WR75 |
| Tx/Rx Isolation | | Rx >40dB Tx >85dB |
| sidelobe($1^\circ \leqslant \theta < 20^\circ$) | | First sidelobe<-20 dB |
| ENVIRONMENTAL | | |
| Temperature operational | | -30° C--50° C |
| Wind load operational | | 20m/s |
| MECHANICAL | | |
| Antenna Type | | Offset antenna |
| Elevation | | 0--90° |
| Azimuth | | ±60° (Vernier adjustment) |
| Polarization | | ±90° |
| Main reflector material | | Carbon Fiber |
| Weight | | 8. 5 Kg |
| Case size | | 675*435*250mm |